



Solutions for a Safer Earth®

# SBR 44

## Spray Buff/Restorer Concentrate

Polaco Rociado/Restaurador

- Restores Wet Look Gloss • Low V.O.C.
- Environmentally Responsible Ingredients



## Technical Data & Training Sheet

### PRODUCT DESCRIPTION:

SBR 44 is a zinc-free high molecular acrylic polymer formulation designed to clean and restore the “wet look” gloss to existing floor finish. Its excellent polishing and restoring ability removes surface marks, leaving floors conditioned, dry and spotless further prolonging the life of the finish. This highly concentrated, economical product can be diluted for application as both a spray buff and high speed restorer.

### USES:

Suitable for use on most floor surfaces including vinyl composition tile, ceramic & quarry tile, terrazzo, concrete, and more.

### ADVANTAGES:

Formulated with a completely biodegradable detergent system for environmental responsibility. Dye and fragrance free. SBR 44 leaves no residue, improving traction and slip-resistance.

### SPECIFICATIONS:

pH: 8-8.5  
 Color: Opaque, Off-White Liquid  
 Solubility in Water: Complete  
 Odor: Acrylic Odor  
 Flash Point: N/A  
 Viscosity: Thin liquid  
 Weight per Gallon: 8.7 Lbs.

### PRODUCT/CONTAINER

#### DISPOSAL:

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.



#### SIZES AVAILABLE:

1 Gallon, 5 Gallons, 30 & 55 Gallons.



Recyclable packaging

### DIRECTIONS FOR PRODUCT USE:

PURPOSE	DILUTIONS
 Spray Buff Polaco Rociado	1:8 (16 oz. SBR 44 per Gallon)
 High Speed Restorer Restaurador	1:4 (32 oz. SBR 44 per Gallon)



It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products. Refer to MSDS for further safety information.

#### DIRECTIONS FOR SPRAY BUFF:



1. Sweep all floors.



2. For maximum results: start with a good base of 3-4 coats of a newly applied high solids floor finish. Let cure 24 hrs.



3. Per chart, prepare solution and apply using a sprayer.



4. Polish or buff with a spray buff pad. If a higher, wet look gloss is desired, re-buff with a fine polishing pad.

Note: Replace pad if it becomes too dirty or too moist.

#### DIRECTIONS FOR RESTORER:



1. Sweep all floors.



2. For maximum results: start with a good base of 3-4 coats of a newly applied high solids floor finish. Let cure 24 hrs.



3. Per chart, prepare solution and apply a thin coat using a clean, wet mop.



4. Allow mopped-on solution to be completely dry. Then polish using a burnishing pad.

### MANUFACTURED BY:

39-30 Review Avenue  
 Long Island City, New York 11101  
 1-888 WAX PLUS • (718) 392-8080 Fax: (718) 482-9366  
 Visit us on the web! [www.focus-ac.com](http://www.focus-ac.com)

